



® **ATLAS WIRE LLC.**
1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#04 133/25 BC .065" PVC RoHS Compliant LOW VOLTAGE BATTERY CABLE SAE J1127 – 105c TYPE SGT

CONDUCTOR: #04 7x19/25 BC 3" LAY
APPROXIMATE NOMINAL O.D. .265"
APPROXIMATE CIRCULAR MILL AREA 42,615
WEIGHT PER THOUSAND FEET 131.60#
BASIC SPECIFICATION ASTM B 173

PVC: TEMPERATURE RATING 105c
ELONGATION 320% AVERAGE
SPECIFIC GRAVITY 1.34
DUROMETER (SHORE) 85 (A)
TENSILE STRENGTH 2450 PSI
OXYGEN INDEX 25
BRITTLE POINT -25c
SPARK TESTED 12,500 VOLTS
NOMINAL FINISHED O.D. .395"
WEIGHT PER THOUSAND FEET 172.13#

info@atlaswirecorp.com