



® **ATLAS WIRE LLC.**
1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#04 133/25 TINNED COPPER 4/64" PVC

RoHS COMPLIANT

**MTW 600v N.E.C. STANDARD or BOAT CABLE-5W2 or
AWM 1283/1232/1015/1337/1346 600v or AWM 1032 1000v VW-1
CSA TEW 105c 600v or AWM I A/B OIL & WATER RESISTANT 75c FT-1**

CONDUCTOR:	#04 7x19/25 TINNED COPPER CONDUCTOR
	APPROXIMATE NOMINAL O.D. .265"
	APPROXIMATE CIRCULAR MILL AREA 42,615
	WEIGHT PER THOUSAND FEET 131.60#
	BASIC SPECIFICATION ASTM B 173
PVC:	TEMPERATURE RATING 105c
	VOLTAGE RATING 600v
	ELONGATION 320% AVERAGE
	SPECIFIC GRAVITY 1.34
	DUROMETER (SHORE) 85 (A)
	TENSILE STRENGTH 2450 PSI AVERAGE
	OXYGEN INDEX 25
	BRITTLE POINT -25c
	SPARK TESTED 12,500 VOLTS
	FINISHED O.D. .388"
	WEIGHT PER THOUSAND FEET 169.60#

USE: INTERNAL WIRING OF APPLIANCES OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. OIL & MOISTURE RESISTANT 75c.

UL 1283, 1015 - 2,500v PEAK FOR ELECTRONIC USE ONLY
UL 1232, 1337 - MOISTURE RESISTANT 60c
UL 1346 - MOISTURE RESISTANT 75c
UL 1032 - 3,500v PEAK FOR ELECTRONIC USE ONLY