



® **ATLAS WIRE LLC.**

1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#10 105/30 TC 1/32" XLPE
RoHS COMPLIANT
CROSS LINKED POLYETHYLENE INSULATED
UL APPLIANCE WIRE STYLE 3321 150c-600v
CSA TYPE CL 1503 600V 150c AWM I - A/B FT2

CONDUCTOR: #10 105/30 TC 2" LAY BUNCHED
APPROXIMATE NOMINAL O.D. .121"
APPROXIMATE CIRCULAR MILL AREA 10,500
WEIGHT PER THOUSAND FEET 32.20#
BASIC SPECIFICATION ASTM B 174

MOISTURE CURED
CROSS LINKED POLYETHYLENE:

TEMPERATURE RATING 125c
VOLTAGE RATING 600 VOLTS
SPECIFIC GRAVITY 1.09
DUROMETER INSTANTANEOUS 53 SHORE D
DUROMETER 10 SECOND DELAY 48 SHORE D
TENSILE STRENGTH 2300 PSI AVERAGE
TENISLE ELONGATION AT BREAK 425%
SPARK TESTED 8,000 VOLTS
FINISHED O.D. .182"
WEIGHT PER THOUSAND FEET 39.34#

UL 3173 USE: INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO
TEMPERATURES NOT EXCEEDING 150c.