



ATLAS WIRE CORPORATION  
9525 RIVER STREET  
SCHILLER PARK, ILLINOIS 60176  
(847) 678-1210  
(847) 678-1281 FAX  
info@atlaswirecorp.com



ATLAS WIRE CORPORATION  
REGISTERED TO ISO 9002  
CERTIFICATE NO. A4894

## MATERIAL SPECIFICATION SHEET

**#14 SOLID BC .035" XLPE  
RoHS COMPLIANT  
CROSS LINKED POLYETHYLENE INSULATED  
PET FENCE WIRE – 125c**

**CONDUCTOR:** #14 SOLID BARE COPPER  
NOMINAL O.D. .0641"  
APPROXIMATE CIRCULAR MILL AREA 4,106  
WEIGHT PER THOUSAND FEET 12.55#  
BASIC SPECIFICATION ASTM B 3

**MOISTURE CURED  
CROSS LINKED POLYETHYLENE:**

TEMPERATURE RATING 125c  
SPECIFIC GRAVITY 1.09  
TENSILE STRENGTH 2300 PSI AVERAGE  
TENSILE ELONGATION AT BREAK 425%  
SPARK TESTED 10,000 VOLTS  
FINISHED O.D. .134"  
WEIGHT PER THOUSAND FEET 17.89#

**PACKAGING:** 10" x 6" SPOOLS  
1,000 FEET PER SPOOL  
SPOOLS CAN BE INDIVIDUALLY PACKED IN A CARTON