



ATLAS WIRE CORPORATION
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
info@atlaswirecorp.com



ATLAS WIRE CORPORATION
REGISTERED TO ISO 9002
CERTIFICATE NO. A4894

MATERIAL SPECIFICATION SHEET

**#14 SOLID BC .044" XLPE
RoHS COMPLIANT
CROSS LINKED POLYETHYLENE INSULATED
PET FENCE WIRE – 125c**

CONDUCTOR: #14 SOLID BARE COPPER
NOMINAL O.D. .0641"
APPROXIMATE CIRCULAR MILL AREA 4,106
WEIGHT PER THOUSAND FEET 12.55#
BASIC SPECIFICATION ASTM B 3

**MOISTURE CURED
CROSS LINKED POLYETHYLENE:**

TEMPERATURE RATING 125c
SPECIFIC GRAVITY 1.09
TENSILE STRENGTH 2300 PSI AVERAGE
TENSILE ELONGATION AT BREAK 425%
SPARK TESTED 10,000 VOLTS
FINISHED O.D. .152"
WEIGHT PER THOUSAND FEET 19.84#

PACKAGING: 10" x 6" SPOOLS
1,000 FEET PER SPOOL
SPOOLS CAN BE INDIVIDUALLY PACKED IN A CARTON