



ATLAS WIRE LLC.  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**#14 41/30 TC 5/64" PVC**  
**RoHS COMPLIANT**  
**MACHINE TOOL WIRE 600V N.E.C. STANDARD &**  
**AWM STYLES 1060 & 1276 105C – 600V VW-1 MOISTURE RESISTANT 60C**  
**& CSA AWM 105C-600V FT1**

<b>CONDUCTOR:</b>	#14 41/30 TC 1-1/2" BUNCHED	
	APPROXIMATE NOMINAL O.D.	.075"
	APPROXIMATE CIRCULAR MILL AREA	4,100
	WEIGHT PER THOUSAND FEET	12.80#
	BASIC SPECIFICATION	ASTM B 174
<b>PVC:</b>	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	320% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	85 (A)
	OXYGEN INDEX	25
	BRITTLE POINT	-25c
	SPARK TESTED	12,500 VOLTS
	NOMINAL O.D.	.238"
	WEIGHT PER THOUSAND FEET	36.90#
<b>USE:</b>	INTERNAL WIRING OF ELECTRIC REFRIGERATING EQUIPMENT or ROOM AIR CONDITIONERS or ROOM COOLER UNITS or REMOTE OUTDOOR CONDENSING UNITS FOR DOMESTIC COOLING SYSTEMS or WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. MOISTURE RESISTANCE 60c.	