



® **ATLAS WIRE LLC.**

1601 Glenlake Av.  
Itasca, ILLINOIS 60143  
(847) 678-1210  
(847) 678-1281  
www.atlaswirecorp.com



Atlas Wire, LLC  
Registered to ISO9001:2015  
and IATF 16949:2016  
Itasca, IL 60143  
Reference No. 10000854



Atlas Wire, LLC  
Registered to ISO9001:2015  
Tucson, AZ 85714  
Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**#14 41/30 TC 1/32" XLPE**

**RoHS COMPLIANT**

**CROSS LINKED POLYETHYLENE INSULATED**

**UL APPLIANCE WIRE STYLE 3321 150c-600v**

**CSA TYPE CL 1503 600V 150c AWM I - A/B FT2**

<b>CONDUCTOR:</b>	#14 41/30 TC 1-1/2" LAY BUNCHED
	APPROXIMATE NOMINAL O.D. .075"
	APPROXIMATE CIRCULAR MILL AREA 4,100
	WEIGHT PER THOUSAND FEET 12.80#
	BASIC SPECIFICATION ASTM B 174

### MOISTURE CURED

### CROSS LINKED POLYETHYLENE:

TEMPERATURE RATING	125c
VOLTAGE RATING	600 VOLTS
SPECIFIC GRAVITY	1.09
DUROMETER INSTANTANEOUS	53 SHORE D
DUROMETER 10 SECOND DELAY	48 SHORE D
TENSILE STRENGTH	2300 PSI AVERAGE
TENSILE ELONGATION AT BREAK	425%
SPARK TESTED	8,000 VOLTS
FINISHED O.D.	.137"
WEIGHT PER THOUSAND FEET	17.78#

**UL 3173 USE:** INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO TEMPERATURES NOT EXCEEDING 150c.