



ATLAS WIRE CORPORATION  
9525 RIVER STREET  
SCHILLER PARK, ILLINOIS 60176  
(847) 678-1210  
(847) 678-1281 FAX  
info@atlaswirecorp.com



ATLAS WIRE CORPORATION  
REGISTERED TO ISO 9002  
CERTIFICATE NO. A4894

## MATERIAL SPECIFICATION SHEET

**#16 19/011 BC .023" XLPE  
RoHS COMPLIANT  
CROSS LINKED POLYETHYLENE INSULATED  
PET FENCE WIRE – 125c**

**CONDUCTOR:** #16 19/011 BARE COPPER 1-1/2" BUNCHED  
NOMINAL O.D. .056"  
APPROXIMATE CIRCULAR MILL AREA 2,299  
WEIGHT PER THOUSAND FEET 7.53#  
BASIC SPECIFICATION ASTM B 174

**MOISTURE CURED  
CROSS LINKED POLYETHYLENE:**

TEMPERATURE RATING	125c
SPECIFIC GRAVITY	1.09
TENSILE STRENGTH	2300 PSI AVERAGE
TENSILE ELONGATION AT BREAK	425%
SPARK TESTED	8,000 VOLTS
FINISHED O.D.	.102"
WEIGHT PER THOUSAND FEET	10.28#

**PACKAGING:** 6" x 6" PLASTIC SPOOLS  
1,000 FEET PER SPOOL  
4 SPOOLS PACKED IN A CARTON