



® **ATLAS WIRE LLC.**

1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#16 19/011 BC .032" XLPE RoHS COMPLIANT CROSS LINKED POLYETHYLENE INSULATED PET FENCE WIRE – 125c

CONDUCTOR:	#16 19/011 BARE COPPER 1-1/2"
	NOMINAL O.D. .056"
	APPROXIMATE CIRCULAR MILL AREA 2,299
	WEIGHT PER THOUSAND FEET 7.53#
	BASIC SPECIFICATION ASTM B 174

MOISTURE CURED CROSS LINKED POLYETHYLENE:

TEMPERATURE RATING	125c
SPECIFIC GRAVITY	1.09
TENSILE STRENGTH	2300 PSI AVERAGE
TENSILE ELONGATION AT BREAK	425%
SPARK TESTED	10,000 VOLTS
FINISHED O.D.	.120"
WEIGHT PER THOUSAND FEET	11.79#

PACKAGING: 10" x 6" SPOOLS
1,000 FEET PER SPOOL
SPOOLS CAN BE PACKED IN INDIVIDUAL CARTONS

www.atlaswirecorp.com

Revision 09/29/2023