



® **ATLAS WIRE LLC.**
 1601 Glenlake Av.
 Itasca, ILLINOIS 60143
 (847) 678-1210
 (847) 678-1281
 www.atlaswirecorp.com



Atlas Wire, LLC
 Registered to ISO9001:2015
 and IATF 16949:2016
 Itasca, IL 60143
 Reference No. 10000854



Atlas Wire, LLC
 Registered to ISO9001:2015
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#16 26/30 TC 1/64" PVC WITH .031" PVC JACKET
RoHS COMPLIANT
DOUBLE INSULATED UL APPLIANCE WIRE
AWM STYLE 1509 105c-300v VW-1
CSA AWM I A/B 105c-300v FT-1

CONDUCTOR: #16 26/30 TINNED COPPER 1-1/4" BUNCHED LAY
 NOMINAL O.D. .059"
 APPROXIMATE CIRCULAR MILL AREA 2,600
 WEIGHT PER THOUSAND FEET 8.10#
 BASIC SPECIFICATION ASTM B 174

PVC: TEMPERATURE RATING 105c
 VOLTAGE RATING 300 VOLTS
 ELONGATION 330%
 SPECIFIC GRAVITY 1.32
 DUROMETER DELAYED (SHORE) 91 (A)
 TENSILE STRENGTH 2450 PSI
 OXYGEN INDEX 28
 BRITTLE POINT -24c
 SPARK TESTED 7,100 VOLTS
 FINISHED O.D. .092"

PVC JACKET: TEMPERATURE RATING 105c
 UL1569 105c
 VOLTAGE RATING 300 VOLTS
 FINISHED OD .154"
 SPARK TESTED 10,000 VOLTS
 WEIGHT PER THOUSAND FEET 17.51#

USE: INTERNAL WIRING OF APPLIANCES
 (REINFORCED INSULATION) – 105c-300v