



® **ATLAS WIRE LLC.**
1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#16 26/30 TINNED COPPER 1/32" PVC
RoHS COMPLIANT
2/CONDUCTOR BONDED RIBBON CABLE
AWM STYLE 2474 105c-600v OR AWM 105c-600v OR TEW 105c

CONDUCTOR:	#16 26/30 TINNED COPPER 1-1/4" LAY	
	NOMINAL O.D.	.059"
	APPROXIMATE CIRCULAR MILL AREA	2,600
	WEIGHT PER THOUSAND FEET	8.10#
	BASIC SPECIFICATION	ASTM B 174
INSULATED SINGLES:	AWM STYLE 1015 105c-600v OR AWM STYLE 1230 105c-600v OR CSA TEW 105c OR CSA AWM 1 A/B 105c-600v	
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	WALL THICKNESS	.031"
	ELONGATION	330% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	8,000 VOLTS
	FINISHED O.D.	.121"
BONDED CABLE:	WEIGHT PER THOUSAND FEET	13.40#
	SPARK TESTED	8,000 VOLTS
	HEIGHT DIMENSION	.121"
	WIDTH DIMENSION	.242"
	WEIGHT PER THOUSAND FEET	26.80#
UL 2474 USE:	INTERNAL WIRING OF ELECTRONIC EQUIPMENT AND APPLIANCES.	

info@atlaswirecorp.com

Revision 09-29-2023