



® **ATLAS WIRE LLC.**  
 1601 Glenlake Av.  
 Itasca, ILLINOIS 60143  
 (847) 678-1210  
 (847) 678-1281  
 www.atlaswirecorp.com



## MATERIAL SPECIFICATION SHEET

**#16 26/30 TINNED COPPER 1/64" PVC  
 RoHS COMPLIANT  
 2/CONDUCTOR BONDED RIBBON CABLE  
 AWM STYLE 2957 105c-300v OR AWM 80c-300v OR CSA TR64 90c**

<b>CONDUCTOR:</b>	#16 26/30 TINNED COPPER 1-1/4" LAY NOMINAL O.D. .059" APPROXIMATE CIRCULAR MILL AREA 2,600 WEIGHT PER THOUSAND FEET 8.10# BASIC SPECIFICATION ASTM B 174
<b>INSULATED SINGLES:</b>	AWM STYLE 1569 105c-300v OR AWM STYLE 1007 80c-300v OR CSA TR64 90c OR CSA AWM 1 A/B 105c-300v
<b>PVC:</b>	TEMPERATURE RATING 105c VOLTAGE RATING 300 VOLTS WALL THICKNESS .016" ELONGATION 330% AVERAGE TENSILE STRENGTH 2450 PSI AVERAGE SPECIFIC GRAVITY 1.32 DUROMETER (SHORE) 91 (A) OXYGEN INDEX 28 BRITTLE POINT -24c SPARK TESTED 5,000 VOLTS FINISHED O.D. .092" WEIGHT PER THOUSAND FEET 10.40#
<b>BONDED CABLE:</b>	SPARK TESTED 5,000 VOLTS HEIGHT DIMENSION .092" WIDTH DIMENSION .184" WEIGHT PER THOUSAND FEET 20.90#
<b>UL 2957 USE:</b>	INTERNAL WIRING OF ELECTRONIC COMPUTERS AND ELECTRIC BUSINESS MACHINES.

info@atlaswirecorp.com