



® **ATLAS WIRE LLC.**  
 1601 Glenlake Av.  
 Itasca, ILLINOIS 60143  
 (847) 678-1210  
 (847) 678-1281  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001:2015  
 and IATF 16949:2016  
 Itasca, IL 60143  
 Reference No. 10000854



Atlas Wire, LLC  
 Registered to ISO9001:2015  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**ATLAS PN 1816T1015-COLOR**  
**#18 16/30 TC 1/32" PVC**  
**RoHS COMPLIANT**  
**MACHINE TOOL WIRE 600V N.E.C. STANDARD &**  
**AWM STYLES 1015 & 1230 105C – 600V OR AWM 1032 90C – 1,000V OR**  
**AWM 1013 & 1011 & 1335 90C – 600V**  
**CSA TEW OR AWM I A/B 105C-600V FT1 CSA OIL & WATER**  
**RESISTANT 75C FT1 CSA TR-32 90c**

<b>CONDUCTOR:</b>	#18 16/30 TC 1"	
	APPROXIMATE NOMINAL O.D.	.048"
	APPROXIMATE CIRCULAR MILL AREA	1,600
	WEIGHT PER THOUSAND FEET	5.00#
	BASIC SPECIFICATION	ASTM B 174
<b>PVC:</b>	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	330% AVG
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	TENSILE STRENGTH	2,450 PSI AVG
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	10,000 VOLTS
	FINISHED O.D.	.110"
	WEIGHT PER THOUSAND FEET	9.70#
<b>USE:</b>	INTERNAL WIRING OF APPLIANCES; OR INTERNAL WIRING OF APPLIANCES WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c.	
<b>UL1230,1335 :</b>	MOISTURE RATING 60c.	
<b>UL1032 :</b>	3,500v PEAK FOR ELECTRONIC USE ONLY	
<b>UL 1015, 1013:</b>	2,500v PEAK FOR ELECTRONIC USE ONLY	

info@atlaswirecorp.com