



® **ATLAS WIRE LLC.**
1601 Glenlake Av.
Itasca, ILLINOIS 60143
(847) 678-1210
(847) 678-1281
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001:2015
and IATF 16949:2016
Itasca, IL 60143
Reference No. 10000854



Atlas Wire, LLC
Registered to ISO9001:2015
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#18 16/30 TC 5/64" PVC
RoHS COMPLIANT
MACHINE TOOL WIRE 600V N.E.C. STANDARD &
AWM STYLES 1060 & 1276 105C – 600V VW-1 MOISTURE RESISTANT 60C
& CSA AWM 105C-600V FT1

CONDUCTOR:	#18 16/30 TC 1" BUNCHED	
	APPROXIMATE NOMINAL O.D.	.048"
	APPROXIMATE CIRCULAR MILL AREA	1,600
	WEIGHT PER THOUSAND FEET	5.00#
	BASIC SPECIFICATION	ASTM B 174
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	320% AVERAGE
	TENSILE STRENGTH	2450 PSI AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	85 (A)
	OXYGEN INDEX	25
	BRITTLE POINT	-25c
	SPARK TESTED	12,500 VOLTS
	NOMINAL O.D.	.211
	WEIGHT PER THOUSAND FEET	24.95#
USE:	INTERNAL WIRING OF ELECTRIC REFRIGERATING EQUIPMENT or ROOM AIR CONDITIONERS or ROOM COOLER UNITS or REMOTE OUTDOOR CONDENSING UNITS FOR DOMESTIC COOLING SYSTEMS or WHERE EXPOSED TO OIL AT A TEMPERATURE NOT EXCEEDING 60c. MOISTURE RESISTANCE 60c.	