



ATLAS WIRE LLC.
 9525 RIVER STREET
 SCHILLER PARK, ILLINOIS 60176
 (847) 678-1210
 (847) 678-1281 FAX
 www.atlaswirecorp.com



Atlas Wire, LLC
 Registered to ISO9001 and TS16949
 Schiller Park, IL 60176
 Reference No. 10000854
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#20 10/30 TC 1/64" PVC WITH .031" PVC JACKET
RoHS COMPLIANT
DOUBLE INSULATED UL APPLIANCE WIRE
AWM STYLE 1509 105c-300v VW-1
CSA AWM I A/B 105c-300v FT-1

CONDUCTOR: #20 10/30 TINNED COPPER 1/2" BUNCHED LAY
 NOMINAL O.D. .038"
 APPROXIMATE CIRCULAR MILL AREA 1,000
 WEIGHT PER THOUSAND FEET 3.20#
 BASIC SPECIFICATION ASTM B 174

PVC: TEMPERATURE RATING 105c
 VOLTAGE RATING 300 VOLTS
 ELONGATION 330%
 SPECIFIC GRAVITY 1.32
 DUROMETER DELAYED (SHORE) 91 (A)
 TENSILE STRENGTH 2450 PSI
 OXYGEN INDEX 28
 BRITTLE POINT -24c
 SPARK TESTED 7,100 VOLTS
 FINISHED O.D. .070"

PVC JACKET: TEMPERATURE RATING 105c
 VOLTAGE RATING 300 VOLTS
 FINISHED OD .132"
 SPARK TESTED 10,000 VOLTS
 WEIGHT PER THOUSAND FEET 10.75#

USE: INTERNAL WIRING OF APPLIANCES
 (REINFORCED INSULATION) – 105c-300v

info@atlaswirecorp.com

Revision 02-22-16