



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#22 7/30 TINNED COPPER .010" PVC
RoHS COMPLIANT
AWM STYLE 10002 105c-300v OR
AWM STYLE 1061 80c-300v VW-1
CSA AWM 80c-300v I A/B FT-1 SR PVC

CONDUCTOR:	#22 7/30 TINNED COPPER 3/4" CONCENTRIC NOMINAL O.D.	.030"
	APPROXIMATE CIRCULAR MILL AREA	700
	WEIGHT PER THOUSAND FEET	2.2#
	BASIC SPECIFICATION	ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	300v
	ELONGATION	300% AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	60 (D)
	TENSILE STRENGTH	3,210 PSI
	OXYGEN INDEX	28
	BRITTLE POINT	-8c
	SPARK TESTED	3,500 VOLTS
	FINISHED O.D.	.050"
	WEIGHT PER THOUSAND FEET	2.97#
USE:	INTERNAL WIRING OF ELECTRIC BOOKEEPING, ACCOUNTING, TIME RECORDING MACHINES OR ELECTRONIC EQUIPMENT IF WITHIN A CHASSIS OR PROTECTED FROM MECHANICAL INJURY.	

Info@atlaswirecorp.com

Revision 02-22-16