



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#22 7/30 TC/BC .017" PVC RoHS COMPLIANT 2/CONDUCTOR RIP CORD

| | | |
|-----------------------|---------------------------------|------------------------|
| ONE CONDUCTOR: | #22 7/30 TINNED COPPER 3/4" LAY | |
| | NOMINAL O.D. | .030" |
| | APPROXIMATE CIRCULAR MILL AREA | 700 |
| | WEIGHT PER THOUSAND FEET | 2.2# |
| | BASIC SPECIFICATIONS | ASTM B-8 ASTM B-286 |
| ONE CONDUCTOR: | #22 7/30 BARE COPPER 3/4" LAY | |
| | NOMINAL O.D. | .030" |
| | APPROXIMATE CIRCULAR MILL AREA | 700 |
| | WEIGHT PER THOUSAND FEET | 2.2# |
| | BASIC SPECIFICATIONS | ASTM B-8 ASTM B-286 |
| PVC: | TEMPERATURE RATING | 105c |
| | VOLTAGE RATING | 300 VOLTS |
| | WALL THICKNESS | .017" |
| | ELONGATION | 330% AVERAGE |
| | TENSILE STRENGTH | 2450 PSI AVERAGE |
| | SPECIFIC GRAVITY | 1.32 |
| | DUROMETER (SHORE) | 91 (A) |
| | OXYGEN INDEX | 28 |
| | BRITTLE POINT | -24c |
| | SPARK TESTED | 3,000 VOLTS |
| DIMENSIONS: | FINISHED NOMINAL O.D. HEIGHT | .064" |
| | FINISHED NOMINAL O.D. WIDTH | .135" |
| | WEIGHT | 7.44# |

info@atlaswirecorp.com

Revision 02-19-16