



ATLAS WIRE LLC.  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**#22 7/30 TC .031" PVC .004" NYLON**  
**RoHS COMPLIANT**  
**MIL-16878/19 TYPE DN**  
**105c - 3,000 VOLTS**

<b>CONDUCTOR:</b>	#22 7/30 TINNED COPPER 3/4" CONCENTRIC NOMINAL O.D. .030" APPROXIMATE CIRCULAR MILL AREA 700 WEIGHT PER THOUSAND FEET 2.20# BASIC SPECIFICATION ASTM B-8 ASTM B-286
<b>PVC:</b>	TEMPERATURE RATING 105c VOLTAGE RATING 3000 VOLTS ELONGATION 330% AVG. SPECIFIC GRAVITY 1.32 DUROMETER (SHORE) 91 (A) TENSILE STRENGTH 2450 PSI AVG SPARK TESTED 15,000 VOLTS OXYGEN INDEX 28 BRITTLE POINT -24c FINISHED O.D. .092" WEIGHT PER 1,000 FEET 5.77#
<b>NYLON:</b>	ELONGATION 300% TENSILE STRENGTH 7400 PSI @ 50% RELATIVE HUMIDITY SPECIFIC GRAVITY 1.13 OVERALL DIAMETER .100" WEIGHT PER M FEET 6.31#
<b>REVISION:</b>	MIL-DTL-16878G - PRINT REQUIRED*

\* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED  
 PLEASE CALL THAT OUT AT TIME OF ORDER.

MEETS ALL REQUIREMENTS LISTED ON THE MIL-DTL-16878/19B DETAIL SPECIFICATION SHEET WITH THE EXCEPTION OF ATLAS CONDITIONING FOR THE HEAT RESISTANCE TEST AT 136c.

[www.atlaswirecorp.com](http://www.atlaswirecorp.com)

Revision 02/22/16