



ATLAS WIRE LLC.
 9525 RIVER STREET
 SCHILLER PARK, ILLINOIS 60176
 (847) 678-1210
 (847) 678-1281 FAX
 www.atlaswirecorp.com



Atlas Wire, LLC
 Registered to ISO9001 and TS16949
 Schiller Park, IL 60176
 Reference No. 10000854
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#24 7/32 TINNED COPPER 1/64" PVC
RoHS COMPLIANT
AWM STYLE 1569 105c-300v
AWM STYLE 1007 80c-300v VW-1 OR
CSA TR 64 90c OR CSA AWM 1 A/B 105c-300v FT-1

CONDUCTOR:	#24 7/32 TINNED COPPER 3/4" LAY	
	NOMINAL O.D.	.024"
	APPROXIMATE CIRCULAR MILL AREA	442
	WEIGHT PER THOUSAND FEET	1.40#
	BASIC SPECIFICATION	ASTM B 8 ASTM B 286
PVC:	TEMPERATURE RATING	UL1007 80c UL1569 105c
	VOLTAGE RATING	300 VOLTS
	ELONGATION	330% AVERAGE
	SPECIFIC GRAVITY	1.32
	DUROMETER (SHORE)	91 (A)
	TENSILE STRENGTH	2450 PSI AVERAGE
	OXYGEN INDEX	28
	BRITTLE POINT	-24c
	SPARK TESTED	7,100 VOLTS
	FINISHED OD	.056"
	WEIGHT PER THOUSAND FEET	2.61#
USE:	INTERNAL WIRING OF APPLIANCES; OR WHERE EXPOSED TO OIL AT TEMPERATURES NOT EXCEEDING 60c. WHERE NOT SUBJECT TO MOVEMENT OR MECHANICAL DAMAGE. 600v PEAK FOR ELECTRONIC USE ONLY.	

info@atlaswirecorp.com