



ATLAS WIRE LLC.  
 9525 RIVER STREET  
 SCHILLER PARK, ILLINOIS 60176  
 (847) 678-1210  
 (847) 678-1281 FAX  
 www.atlaswirecorp.com



Atlas Wire, LLC  
 Registered to ISO9001 and TS16949  
 Schiller Park, IL 60176  
 Reference No. 10000854  
 Tucson, AZ 85714  
 Reference No. 10003647

## MATERIAL SPECIFICATION SHEET

**#24 7/32 TC .017" PVC .003" NYLON**  
**RoHS COMPLIANT**  
**MIL-16878/18 TYPE CN**  
**105c - 1,000 VOLTS**

<b>CONDUCTOR:</b>	#24 7/32 TINNED COPPER 3/4" CONCENTRIC NOMINAL O.D. .024" APPROXIMATE CIRCULAR MILL AREA 442 WEIGHT PER THOUSAND FEET 1.40# BASIC SPECIFICATION ASTM B-8 ASTM B-286
<b>PVC:</b>	TEMPERATURE RATING 105c VOLTAGE RATING 1000 VOLTS ELONGATION 330% AVG. SPECIFIC GRAVITY 1.32 DUROMETER (SHORE) 91 (A) TENSILE STRENGTH 2450 PSI AVG SPARK TESTED 8,500 VOLTS OXYGEN INDEX 28 BRITTLE POINT -24c FINISHED O.D. .058" WEIGHT PER 1,000 FEET 2.72#
<b>NYLON:</b>	ELONGATION 300% TENSILE STRENGTH 7400 PSI @ 50% RELATIVE HUMIDITY SPECIFIC GRAVITY 1.13 OVERALL DIAMETER .064" WEIGHT PER M FEET 2.97#
<b>REVISION:</b>	MIL-DTL-16878G - PRINT REQUIRED*

\* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED  
 PLEASE CALL THAT OUT AT TIME OF ORDER.

MEETS ALL REQUIREMENTS LISTED ON THE MIL-DTL-16878/18B DETAIL SPECIFICATION SHEET WITH THE EXCEPTION OF ATLAS CONDITIONING FOR THE HEAT RESISTANCE TEST AT 136c.

